

develop the coefficient sliding fractions for each case.

REFERENCES

- KHCM (2001)., Korean Society of Transportation.
- Kim, S.Y. (2011) A Methodology for Setting up the Dilemma Zone using Spot Speeds., Seoul National University.
- Kim, J.H., Lee, S.B., Park, B.J. (2002) Improvement of Potentially Hazardous Roadway Segment Identification., *Study of Policy*, KOTI.
- Lee, K.B. (2001) Development of a Procedure in Identifying Black Spots., Yonsei University.
- Lee, K.Y., Chang, M.S. (2005) Selecting Technique of Accident Sections using K-mean Method.. *Korean Society of Road Engineers*, Vol.7, No.4, pp.211-219.
- Lim, C.S., Choi, Y.W. (2010) The Experimental Study on the Transient Brake Time of Vehicles by Road Pavement and Friction Coefficient. *Korean Society of Civil Engineers*, Vol.30, No.6D, pp.587-597
- Oh, D.S., Lee, S.B., Kim, W.C., Hong, D.H. (2002) A Study of Perception Response Time on Various Operating Speeds, *Korean Society of Civil Engineers*, Vol.22, No.6, pp.1105-1116.
- Elvik, R. (2008) A survey of operational definitions of hazardous road locations in some European countries., ELSEVIER., *Accident Analysis and Prevention*., Vol.40, pp. 1830-1835.